



# AirTap Warm-air Hand Dryer 371

110 V with IR sensor  
 Deck-mounted  
 Stainless Steel with satin finish  
 2-year warranty



DAN DRYER AirTap features a minimalist, modern design in stainless steel with satin finish. The intelligent temperature control technology detects the room temperature and adjusts the heating element.

## Application

DAN DRYER AirTap is a powerful hand dryer suitable for toilet rooms with a high visitor frequency. With its elegant slim design, the hand dryer is the perfect choice for all kinds of commercial washrooms. The DAN DRYER Tap range is an ideal build-in solution for construction projects and automatic hand wash stations.

## References

Shopping centres, restaurants, hotels, airports, sports facilities, schools, and public institutions.

## Technical data

	DAN DRYER AirTap Prod. No.: 371 Touch-less warm-air hand dryer with IR sensor
Type	
Dimensions tap	H 6.69" x W 1.96" x D 8.66"
Dimensions motor	H 7.99" x W 12.04" x D 5.90"
Material	Stainless steel, satin finish
Drying cycle	10-15 sec.
Connection	110 V, 50/60 Hz, Class I
Total wattage	600-1000 W
Heating element	100-500 W
Motor	500 W
Noise level	68.5-70.5 dBA
Max. air capacity	84-101 m/sec.
Max. air outlet temperature	57° C
Net weight	13.22 lb
IP rating	IP35

## Standard colour

Stainless steel, satin finish

## Activation

Infrared sensor and electronic timer. Touch-free. Activation distance adjustable 5.11" ( $\pm$  0.78"). Automatic stop after 60 seconds of continuous use.

## Motor type

Commutator motor with carbon brushes. 22,000-29,000 revolutions/min.

## Protection

Automatic thermal cut-out in both motor and heating element.

## Installation

Machine intended for table top mounting. Connection to fixed installation or via circuit-breaker. Installation must be carried out by a qualified electrician.

## Tender text

Touch-less hand dryer in stainless steel with satin finish for deck mounting. Infra-red sensor and electronic timer, drying cycle: 10-15 sec. IP35, 110 V, 50/60 Hz, 1000 W, Class I (earthed). 68.5-70.5 dBA.

Net weight: 13.22 lb. H 6.69" x W 1.96" x D 8.66".

## Approval

UL, CE, GS, BSMI, EMC, LVD, WEEE, RoHS, UKCA

