



# LOKI Warm-Air Hand Dryer, 110 V

## 4001/4003/4005/4007



reddot winner 2021



**High-speed**  
**IR-sensor and electronic timer**  
**5-year warranty**

DAN DRYER LOKI high-speed hand dryer; award winning and ADA compliant. Its elegant and functional design is characterized by clean lines and rectangular shapes, which complements the surrounding architecture. The robust front plate with the high light guide maintains the design theme throughout the LOKI family.


### Application

DAN DRYER LOKI is a compact, high-speed hand dryer in sleek design. Featuring short drying time and low maintenance, this reliable machine is suitable for all high traffic public and commercial areas.

### References

Offices and administration, shopping centres, restaurants, hotels and leisure, airports, schools, and sports facilities.

### Technical data

	LOKI Prod. No.: 4001, 4003, 4005, 4007
Type	Warm-air hand dryer with IR sensor
Dimensions	H 11.81 x W 6.81 X D 4.01"
Material	Brushed or powder coated stainless steel
Drying cycle	10-15 sec.
Connection	110-120 V, 50/60 Hz, Class I 
Total wattage	1000 W
Noise level	69-76.6 dB @ 39"
Max. air capacity	312'-377'/sec.
Net weight	9.9 lb
IP rating	IP24

### Standard colors

Prod. No. 4001: Brushed stainless steel  
 Prod. No. 4003: RAL 9003, white, gloss 60  
 Prod. No. 4005: RAL 9005, matt black, gloss 10  
 Prod. No. 4007: RAL Classic colors

### Activation

Infrared sensor and electronic timer. Touch free. Activation distance adjustable 6.77" ( $\pm$  0.79 "). Automatic stop after 60 seconds of continuous use.

### Motor type

Commutator motor with carbon brushes.  
 16,000-29,000 revolutions/min.

### Protection

Automatic thermal cut-out in both motor and heating element.

### Installation

Machine intended for wall-mounting and fixed installation via circuit-breaker. Installation must be carried out by a qualified electrician.

### Tender text

Touch-free hand dryer in stainless steel, brushed or powder coated Infra-red sensor and electronic timer, drying cycle: 10-15 sec. IP24, 110 V, 50/60 Hz, 840-1000 W, Class I (earthed), 69-76.6 dB @ 39" dBA.  
 Net weight: 9.9 lb. H: 11.81", W: 6.81", D: 4.01".

### Approval

CE, WEEE, RoHS, UKCA