



# LOKI HAND DRYER

## 4000/4002/4004/4006




High-speed  
IR-sensor and electronic timer  
5-year warranty



LOKI high-speed hand dryer; award winning and ADA compliant. Its elegant and functional design is characterised by clean lines and rectangular shapes, which complements the surrounding architecture. The robust front plate with the high light guide maintains the design theme throughout the LOKI range.

### Technical data

Type	<b>LOKI HAND DRYER</b> Prod. No.: 4000, 4002, 4004, 4006  Warm-air hand dryer with IR sensor
Dimensions	H: 300 mm x B: 173 mm x D: 102 mm
Material	Brushed or powder coated stainless steel
Drying cycle	10-15 sec.
Connection	230 V, 50/60 Hz, Class I
Total wattage	840-1000 W
Heating element	500 W
Motor	340-500 W
Noise level	69-76,6 dB @ 1 m
Max. air capacity	95-115 m/sek.
Max. air outlet temperature	55° C
Net weight	4,5 kg
IP rating	IP24
Tender text	Touch-free hand dryer in stainless steel, brushed or powder coated Infra-red sensor and electronic timer, drying cycle: 10-15 sec. IP24, 230 V, 50/60 Hz, 840-1000 W, Class I (earthed), 69-76.6 dB @ 1 m dBA. Net weight: 4.5 kg. H: 300 mm x B: 173 mm x D: 102 mm



### Application

LOKI is a compact, high-speed hand dryer in sleek design. Featuring short drying time and low maintenance, this reliable machine is suitable for all high traffic public and commercial areas.

### References

Offices and administration, shopping centres, restaurants, hotels and leisure, airports, schools, and sports facilities.

### Standard colours

Prod. No.: 4000, Brushed stainless steel.  
Prod. No.: 4002, RAL 9003, white, gloss 60.  
Prod. No.: 4004, RAL 9005, matt black, gloss 10.  
Prod. No.: 4006, RAL Classic colours.

### Activation

Infrared sensor and electronic timer. Touchfree. Activation distance adjustable 172 mm (± 20 mm). Automatic stop after 60 seconds of continuous use.

### Motor type

Commutator motor with carbon brushes. 16,000-29,000 revolutions/min.

### Protection

Automatic thermal cut-out in both motor and heating element.

### Installation

Machine intended for wall-mounting and fixed installation via circuit-breaker. Installation must be carried out by a qualified electrician.

### Compliance

