



# BJÖRK BABY CHANGING STATION WITH SAFETY STRAP

## 3220/3222/3224

Wall mounted  
Powder coated aluminium  
2-year warranty



The BJÖRK baby changing station by DAN DRYER has been awarded several prestigious design prizes. Perfectly adapted ergonomically, it provides a comfortable and secure base for the infant, and with its design approach marked by purism and practical use, it goes far beyond familiar forms by creating a highly refined aesthetic. The baby changing station meets the highest demands, offering a great deal of comfort for both infants and parents. This product is SGS certified, compliant with the American standard ASTM F2285-04 and the European EN 12221-. It also meets ADA regulations when installed according to ADA guidelines.



### Technical data

Metric

Imperial

Type	BJÖRK Prod. No.: 3220, 3222, 3224  Baby changing station with safety strap	BJÖRK Prod. No.: 3220, 3222, 3224  Baby changing station with safety strap
Width	552 mm	21.73"
Depth (folded up)	100 mm	3.93"
Depth (folded down)	751 mm	29.56"
Height (folded up)	771 mm	30.35"
Height (folded down)	322 mm	12.67"
Changing surface	L: 700 mm x B: 510 mm	L 27.55" x W 20.07"
Load capacity	80 kg	176.37 lb
Recommended working height	950 mm above floor	37.40" above floor
Force required to open	~25 N; to close: ~25 N	~25 N; to close: ~25 N
Net weight	17 kg	37.47 lb
Tender text	Baby changing station. Powder coated steel wall unit, powder coated aluminum profile and electro-galvanized steel axle and levers. Load capacity: 80 kg. Net weight: 17 kg.	Baby changing station. Powder coated steel wall unit, powder coated aluminum profile and electro-galvanized steel axle and levers. Load capacity: 176.37 lb. Net weight: 37.47 lb.

### Application

BJÖRK, a true breakthrough in commercial bathroom products. The elegant design line is suitable for all types of public toilets.

### References

Offices and administration, shopping malls, restaurants, hotels, airports, sports facilities and public swimming pools, schools, public institutions and cultural centres.

### Standard colour

Prod. No. 3200: RAL 9003, white, gloss 75.  
Prod. No. 3205: RAL 9005, black, gloss 7-12.  
Prod. No. 3210: RAL Classic colours.

### Materials

Changing surface: Powder coated aluminium profile.  
Wall unit: Powder coated steel plate.  
Axle and levers: Electro-galvanized steel.

### Installation

Wall mounting. The recommended working height above floor: Approx. 950 mm / 37.40".

### Function

Torsion springs ensure the smooth and easy opening and closing motion of the unit.

### Certification

Tested in accordance with DIN EN 12221-1:2008 + A1:2013, and the American standard ASTM F2285-04.

