

SOAPTAP 476

IR sensor
Deck-mounted
Stainless steel with black PVD coating
2-year warranty



SoapTap soap dispenser for fluid soap features a minimalist, modern design in stainless steel black PVD coating. The soap dispenser is part of a complete product range, which also includes hand dryer and water faucet.

Technical data

	Metric	Imperial
Type	SOAPTAP Prod. No.: 476 Touch-free soap dispenser with IR sensor	SOAPTAP Prod. No.: 476 Touch-free soap dispenser with IR sensor
Dimensions spout	H: 170 mm x Ø50/ø38 x D: 220 mm	H: 6.69" x Ø1.96"/ø1.49" x D: 8.66"
Dimensions soap tank	H: 311 mm x W: 117 mm x D: 129 mm	H: 12.24" x W: 4.60" x D: 5.07"
Material	Stainless steel	Stainless steel
Connection	6V DC, AC/DC adaptor	6V DC, AC/DC adaptor
Wattage standby	0.14 W	0.14 W
Viscosity	1-3000 cP	1-3000 cP
Capacity	1,5 l (1000-1500 doses)	0.39 gal (1000-1500 doses)
Net weight	1,9 kg	4.18 lb
IP rating	IP35	IP35
Tender text	Touch-free soap dispenser for liquid soap, in stainless steel with black PVD coating, tabletop-mounted, infra-red sensor, capacity 1,5 l (1000-1500 doses), power supply 6V DC. Net weight: 1.9 kg. H: 170 mm x Ø50/ø38 x D: 220 mm. H: 311 mm x W: 117 mm x D: 129 mm	Touch-free soap dispenser for liquid soap, in stainless steel with black PVD coating, tabletop-mounted, infra-red sensor, capacity 0.39 gal (1000-1500 doses), power supply 6V DC. Net weight: 4.18 lb. H: 6.69" x Ø1.96"/ø1.49" x D: 8.66". H: 12.24" x W: 4.60" x D: 5.07"

Application

SoapTap soap dispenser with automatic sensor for touch-free activation is a hygienic solution for commercial washrooms. The elegant slim design complements any bathroom and gives a modern classy look. The DAN DRYER Tap range is an ideal build-in solution for construction projects and automatic hand wash stations.

References

Shopping centres, restaurants, hotels, airports, sports facilities, schools and public institutions.

Standard colour

Black PVD coating.

Activation

Infra-red sensor and electronic timer. Touchfree. Activation distance adjustable between 20 mm-150 mm / 0.78"-5.90".

Installation

The dispenser is intended for table top mounting. Connection to fixed wiring or via circuit-breaker. Installation must be carried out by a qualified electrician.

Approval

